
MAINTENANCE-FREE MOTORCYCLE BATTERY

UP4-3-I (12V3Ah)







GENERAL FEATURES

- Maintenance-free
- · Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (1	0HR)	3Ah
Cold Cranking Perfo	rmance Amps@0°F (-18°C) 50A
Dimension (±2mm)	Length	113mm (4.45inches)
	Width	70mm (2.76inches)
	Container Height	85mm (3.35inches)
	Total Height	85mm (3.35inches)
Battery (with acid)	Approx Weight	1.32kg (2.91lbs)
Terminal type		A
Battery type	Factory Activated Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C ₁₀
	Voltage 14.40V~15.00V at 25°C (77°F)	
	Charging time	15~18h
	Constant-Current Charg	e:
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage 1	3.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

