
MAINTENANCE-FREE MOTORCYCLE BATTERY



UPZ12-4-1 (12V11Ah)




┣┛┓ Φ ╙╻Ѳ 110 ± 5 88土2 7



CHARACTERISTICS

| Item | | Specifications |
|----------------------------------|---|------------------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (1 | 0HR) | 11Ah |
| Cold Cranking Perfo | rmance Amps@0°F (-18° | C) 210A |
| Dimension (±2mm) | Length | 150mm (5.91inches) |
| | Width | 88mm (3.46inches) |
| | Container Height | 110mm (4.33inches) |
| | Total Height | 110mm (4.33inches) |
| Battery (with acid) | Approx Weight | 3.81kg (8.40lbs) |
| Terminal type | | A |
| Battery type | Factory Activated Serie | es |
| Full Charge | Constant-Voltage Charge: | |
| | Initial charging current | Less than 0.3C10 |
| | Voltage | 14.40V~15.00V at 25°C (77°F) |
| | Charging time | 15~18h |
| | Constant-Current Cha | rge: |
| | Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h | |
| Floating Charge | Initial charging current | Unlimited |
| | Voltage 13.50V~13.80V at 25°C (77°F) | |
| Capacity affected by Temperature | 40°C (104°F) | 106% |
| | 25°C (77°F) | 100% |
| | 0°C (32°F) | 86% |
| | -15°C (5°F) | 65% |

Discharge Characteristics (25°C, 77°F)



GENERAL FEATURES

Maintenance-free

 Φ

 \oplus

· Sealed and non-spillable AGM battery

θ

₽

· Shipped pre-charged and ready to install