FLOODED BATTERY

L7R-055 (12V40Ah)






CHARACTERISTICS

| Item | | Specifications |
|--------------------------------|--------|-------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 40Ah |
| Reserve Capacity | | 61min |
| Cold Cranking Amps@0°F (-18°C) | | 350A |
| | Length | 195mm(7.68inches) |
| Dimension | Width | 126mm(4.96inches) |
| | Height | 222mm(8.74inches) |
| Approx Weight | | 10.1kg(22.3lbs) |
| Terminal | | 3 |
| Cell layout | | 1 |
| Hold-Down | | В0 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS1 |


APPLICATIONS


- Car start
- •EV/HEV
- •Engine start




GENERAL FEATURES

- ·High capacity and high CCA
- ·Long life
- •Advanced lead-calcium alloy technology, maintenance-free design
- Patented venting system bring less water loss and prevent acid leakage
- •OE quality certification







Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.